



Pneumatiska bandare för mobilt & stationärt bruk.



Tekniska specifikationer	STR 64	STR 65	STR 66	STR 67	STR 68	STR 69
För band/modellnr	13x0,63mm 16x0,63mm 19x0,63mm	19x0,80mm	25x1,00mm 32x0,80mm 32x1,00mm	3/4-1 1/4 x0,40	19x1,00mm 25x1,00mm 32x1,00mm	19x1,00mm 25x1,00mm 32x1,00mm
Vikt	3,2kg	7,6kg	9,3kg	4,1kg	2,8kg	4,7kg
Längd/bredd/höjd	302/130/180	420/160/300	470/170/300	340/110/110	300/130/210	350/170/230
Bandspänning	3000N	7000N	8400N	8400N		
Luftförbrukning						
- Vid bandspänning	4 NI/s	6,4 NI/s	6,4 NI/s	6,4 NI/s		
- Vid plombering	3,4 NI	12 NI	14 NI		3 NI	6,4 NI
Stålband						
Draghållfasthet 850N/mm2 upp till 1100 N/mm2	19x0,63mm 19x0,63mm	19x0,80mm 19x0,80mm	32x1,00mm 32x0,80mm	32x1,00mm 32x1,00mm	32x1,00mm 32x0,80mm	32x1,00mm 32x0,80mm
Plomber						

