



TP-601BP TAURIS TRANSIT with PRESS
Fully automatic machine for wide straps
Belt-Driven Table with Press

Main Features




Auto Strap Feeding
 Simply insert the strap into the feeding rollers from the coil side of the machine and then push the "reset" button. The machine will automatically feed itself without access to the inside of the machine. The Tauris Transit models, used in conjunction with feed conveyors, do not have to be removed from the line for strap feeding.




Electronic Tension Control
 External adjustment of strap tension by the simple turn of a dial.



Auto Strap Ejector
 Loop-eject clears unwanted strap automatically, if the machine is accidentally strapped without a package.



Belt Transmission
 Instead of using roller chain, belt transmission systems ensure long operational life and quiet operation.



Hinged Top Plates
 Opens wide for quick cleaning, inspection, and maintenance of strapping head, strap-feed and tensioning unit.



Multiple strap function for single, double, triple strapping or transit

Options

- ❖ Siemens PLC control
- ❖ Variable conveyor speed: from 18 meters/minute to 42 meters/minute
- ❖ Stainless steel frame SUS 304 (TP-601BP)

Arch Sizes

H/W	850	1050	1250
400			
600	Ⓢ		
800			
1000			

● Standard size: 850 mm(W) x 600 mm(H)

Technical Data

Strap Width 8 mm-12 mm
 Strap Tension 7 kg-70 kg
 Conveyor Speed 30 meters/minute
 Table Height 825 mm
 Bundle Compression 6 bar
 Air Consumption 10 liter/cycle
 Net Weight 347 kg
 Power Requirement 220V, 380V, 400V; @50/60Hz; @3PH

