



	SD 320	SD 420	SD 620	SD 820	SD 1020
		SID 420	SID 620		
Sealing length: mm	320	420	620	820	1020
Sealing width: mm	2 x 5	2x 5	2 x 5	2 x 5	2 x 5
Max. film width: mm	300	400	600	800	1020
Cutting length: mm	320	420	620	820	1020
Voltage: V/Hz	230 – 50/60	230 – 50/60	230 – 50/60	230 – 50/60	230 – 50/60
Power :W	350	650	500	1000	1200
Dimensions of the machine: HxSzxM mm	520 x 650 x 1100	620 x 650 x 1100	820 x 650 x 1100	1020 x 850 x 1100	1220 x 850 x 1100
Weight: kg	25	30	36	46	48
Maximum foil thickness: Micron	PE - 500 PP - 200 BOPP - 160 PVC - 100	PE - 500 PP - 200 BOPP - 160 PVC - 100	PE - 500 PP - 200 BOPP - 160 PVC - 100	PE - 500 PP - 200 BOPP - 160 PVC - 100	PE - 500 PP - 200 BOPP - 160 PVC - 100

ASM Sweden AB
 Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel. 040 - 22 89 80,
 Fax 040 - 22 89 60

www.asm.eu