

**strapex**

**NEW**

**STB 70**

**A quantum leap  
in strapping**


**Easy**

**Fast**

**Safe**

**Economic**

**Environmentally-friendly**



**Patent pending**

# STB 70

## Quantum leap: Strapping with only one push of a button!

### Easy

- Depending on application, adjustable operation mode
- Fully automatic
- Semi-automatic
- Manual
- Soft



### Fast




Regardless of package, size, vertical or horizontal strapping:

- Fully or semi-automatic tensioning, welding, and strap cutting – with only one push of a button

### Economic

- Energy-efficient strapping system
- More cycles per battery charge
- Cost efficient
- Service-friendly construction
- High quality

### Safe



For multiple strapping or for the same types of goods:

- Consistent strappings
  - Automatic strapping eliminates operator error
- Strapping with PP strap or for fragile packages:
- "Soft" mode

### Environmentally-friendly



Latest brushless motor engineering with the latest environmental-friendly battery technology from Bosch:

- High efficiency ratio
- No memory effect
- Recharging at any time
- High number of strappings



Developed and manufactured in Switzerland

### Technical data

Weight (including battery)	3.9 kg
Dimensions	
– Length	334 mm
– Width	138 mm
– Height	148 mm
Tensioning force	(0) 900–2500 N
– Soft	(0) 400–1500 N
Tensioning speed	220 mm/s
Sealing	Friction-weld-seal

### Battery charger, battery

Charger voltage	100, 110, 230 V
Battery charging time	20–45 minutes*
No of cycles per battery, up to	400**
Battery: Li-Ion (Bosch)	14.4 V, 2.6 Ah

### Plastic strap

	Polypropylene (PP)
	Polyester (PET)
Width	12–13, 15–16 mm
– Option	9–11 mm
Thickness	0.5–1.0 mm

### Options

- Suspension bow
- Protection plate
- Protection cover
- Power supply

\* After 20 minutes, approx 70% charge capacity

\*\* Depending on strap quality, tension and package

### Strapex advantage

Tool, strap and after-sales service as a total package

