

RONDA 4000



The machine shown could be rappedresented in a non - standard version.

RONDA 4000
 Semiautomatic pallet wrapping machine with stretch film for the stabilisation and securing of palletised loads. The model illustrated has the possibility of inserting pallets also with manual transpallets and runs only with the presence of an operator during the work cycle. .

- Strong and rugged construction
- Stabilisation and protection of the pallet
- Fast operations
- Saving in film
- Easy use
- Reduced bulk
- Minimum maintenance



- Mast hinged to base for fast and easy installation
- Table indexed stop
- Open turntable for insertion of transpallet at 90°, 180° and 270°
- Safety device (for breaking falls) in the event of belt breakage
- Transpallet insertion safety photocell
- Roll carriage driven by belt
- Mechanical clutch to adjust film tension
- Inverter for gradual start-up and regulation of rotary table speed
- Pre - arrangement for top pressing device
- Rollcarriage rise/descent button
- Turntable start/stop button
- Electrical panel

Electrical power supply	400 V / 50 Hz
Temperature of use	+5°C/+35°C
Turntable rotation speed	10 r.p.m.
Turntable diameter	1500 mm
Machine plan dimensions	2670 x 1700 x H 2560 mm
Max. Wrapping pallet dimensions	1000 x 1200 x 2250 mm
Weight	560 kg
Loading of the turntable	1500 kg
Installed power	1,0 kW
Film roll height	500 mm
Electrical protection	IP 54
Film roll diameter	300 mm

ASM Sweden AB
 Box 9182, 200 39 Malmö
 Bronsyxegatan 9, 213 75 Malmö
 Tel. 040 - 22 89 80
 Fax 040 - 22 89 60
www.asm.eu