

RONDA 4500

RONDA 4500

Semiautomatic pallet wrapping machine with stretch film for the stabilisation and securing of palletised loads. The model illustrated has the possibility of inserting pallets also with manual transpallets and runs only with the presence of an operator during the work cycle.

- Strong and rugged construction
- Stabilisation and protection of the pallet
- Fast operations
- Saving in film
- Easy use
- Reduced bulk
- Minimum maintenance



The machine shown could be represented in a non - standard version.



- Mast hinged to base for fast and easy installation
- Open turntable for insertion of transpallet at 90°, 180° and 270°
- Safety device (for breaking falls) in the event of belt breakage
- Safety photocell on turntable infeed side
- Photocell for automatic pallet height detection
- Roll carriage driven by belt
- Adjustable electromagnetic clutch for film tension control
- Inverter for gradual start-up and regulation of table speed and indexed stop
- Pre - arrangement for top pressing device
- Electrical panel with digital control panel
- Separate regulation of upper and lower revs number
- Manual/automatic selector

Electrical power supply	400 V / 50 Hz
Temperature of use	from 5°C to +35°C
Turntable rotation speed	from 6 to 14 r.p.m.
Turntable diameter	1500 mm
Machine plan dimensions	2670 x 1700 x H 2560 mm
Max. Wrapping pallet dimensions	1000 x 1200 x 2250 mm
Weight	560 kg
Loading of the turntable	1500 kg
Installed power	1,0 kW
Film roll height	500 mm
Electrical protection	IP 54
Film roll diameter	300 mm

ASM Sweden AB
 Box 9182, 200 39 Malmö
 Bronsyxegatan 9, 213 75 Malmö
 Tel. 040 - 22 89 80
 Fax 040 - 22 89 60
www.asm.eu