

RONDA 5000

RONDA 5000

Semiautomatic pallet wrapping machine with stretch film for the stabilisation and securing of palletised loads. The model illustrated has the possibility of inserting pallets also with manual transpallets and runs both with or without the presence of an operator during the work cycle. A top-range machine with various wrapping cycles.

- Strong and rugged construction
- Stabilisation and protection of the pallet
- Fast operations
- Saving in film
- Easy use
- Reduced bulk
- Minimum maintenance



The machine shown could be represented in a non - standard version.



- Mast hinged to base for fast and easy installation
- Open turntable for insertion of transpallet at 90°, 180° and 270°
- Safety device (for breaking falls) in the event of belt breakage
- Safety photocell on turntable infeed side
- Photocell for automatic pallet height detection
- Roll carriage driven by belt
- Adjustable electromagnetic clutch for film tension control
- Inverter for gradual start-up and regulation of table speed from 6 to 14 r.p.m. and indexed stop
- Pre - arrangement for top pressing device
- Digital electronic panel with display and diagnostic program for automatic faults detection, with 4 different wrapping programs, including rise only wrapping cycle, wrapping cycle for positioning of a waterproof sheet protection on the top of the pallet w
- Separate regulation of upper/lower revs number
- Manual/automatic selector

Electrical power supply	400 V / 50 Hz
Temperature of use	from +5°C to +35°C
Turntable rotation speed	from 6 to 14 r.p.m.
Turntable diameter	1500 mm
Machine plan dimensions	2670 x 1700 x H 2560 mm
Max. Wrapping pallet dimensions	1000 x 1200 x 2250 mm
Weight	560 kg
Loading of the turntable	2000 kg
Installed power	1,0 kW
Film roll height	500 mm
Electrical protection	IP 54
Film roll diameter	300 mm

ASM Sweden AB
 Box 9182, 200 39 Malmö
 Bronsyxegatan 9, 213 75 Malmö
 Tel. 040 - 22 89 80
 Fax 040 - 22 89 60
www.asm.eu