

RONDA 3000 Twin

RONDA 3000 Twin
 Semiautomatic pallet wrapping machine with stretch film for the stabilisation and securing of palletised loads. The model illustrated can be operated with or without an operator. The TWIN version differs from the standard model for the presence of a single column and two turntables. It allows loading/unloading of one pallet on a turntable while, at the same time, the pallet positioned on the other one is wrapping. Top-range machine with various wrapping cycles.

- Strong and rugged construction
- Stabilisation and protection of the pallet
- Fast operations
- Saving in film
- Easy use
- Reduced bulk
- Minimum maintenance



The machine shown could be represented in a non - standard version.



- Machine structure in painted sheet steel
- Mast hinged to base for fast and easy installation
- Roll carriage driven by belt
- Carriage parachute safety device in the event of belt breakage
- Pre - arrangement for top pressing device
- Digital electronic panel with display and diagnostic program for automatic faults detection, with 4 different wrapping programs, including rise only wrapping cycle, wrapping cycle for positioning of a waterproof sheet protection on the top of the pallet w
- Adjustable electromagnetic clutch for film tension control
- Manual/automatic selector
- Separate regulation of upper/lower revs number
- Photocell for automatic pallet height detection
- Inverter for gradual start-up and regulation of table speed and indexed stop

Turntable rotation speed	from 6 to 14 r.p.m.
Turntable diameter	1500/1650 mm
Max. Wrapping pallet dimensions	1000 x 1200 x 2250 mm
Film roll height	500 mm
Film roll diameter	300 mm
Loading of the turntable	2000 kg

ASM Sweden AB
 Box 9182, 200 39 Malmö
 Bronsyxegatan 9, 213 75 Malmö
 Tel. 040 - 22 89 80
 Fax 040 - 22 89 60
www.asm.eu