



ECOGEM 50

Semiautomatic carton sealer with gum paper for the top and bottom sealing of American-type boxes, for uniform carton size batches, manual dimensioning. The adjustments are fast and easy, also allowing its use by non-specialist operators. The machine, if combined with infeed and outfeed conveyors, represents a simple, fast and economical packaging station.

- Economical
- Strong and rugged
- Fast operations
- Optimal sealing
- Easy use
- Simple regulation
- Reduced bulk

TECHNICAL DESCRIPTION

Main machine structure in bent, bolted and painted sheet steel. The boxes are fed by means of 2 bottom side drive belts driven by a single motor. The regulations for the various formats are carried out by means of hand-wheels.

Standard taping heads: H20 for gum paper with width min 38mm, max 75mm

Supports : fixed

Box size: L from 150 mm upwards W from 120 to 650 mm H from 100 to 500 mm

Production rate up to 700 boxes an hour

Box transfer speed 17 metres a minute

Electrical power supply three-phase / single-phase

Temperature of use from + 5°C to + 35°C

Electrical protection IP 54

Installed power 1 kW

Overall plan dimensions 1200 x 910 mm

Work surface height 650 mm

Weight 174 kg

*The specifications may be subject to change.

ACCESSORIES

RUL, Roller conveyors for box entrance and exit - S04, Casters - S15, Opposite sided versions - S20

ASM Sweden AB

Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel. 040 - 22 89 80, Fax 040 - 22 89 60

Försäljningskontor: Göteborg Tel. 0301 - 212 11 Halmstad 035 - 22 78 70 Stockholm Tel. 08 - 647 95 60 Östersund Tel. 063 - 10 46 05

www.asm.eu