




GEM F470



Automatic carton sealer with manual dimensioning and flap closer. It folds automatically the four upper flaps and seals with auto-adhesive tape the top and bottom of batches of uniform size, American-type boxes. The regulations are fast and easy. To be used on fully automatic lines not controlled by operatives. .

- Very economical
- Strong and rugged
- Fast operations
- Optimal sealing
- Easy use
- Simple regulation
- Reduced bulk

TECHNICAL DESCRIPTION

Main machine structure in bent, bolted and painted sheet steel. The boxes are fed by 2 lower side drive belts driven by a single motor. The regulations for the various formats are carried out by means of handwheels.

Folding of the upper flaps: mobile flap folder with pneumatic actuation

Box feed: 2 side drive belts, parallel and self-centring

Standard taping heads: T22 or T23 for adhesive tape with width 50 mm

Supports: fixed

Box size: L from 150 to 600 mm W from 100 to 520 mm H from 100 to 670 mm

Guards: movable hinged panels with safety microswitches

Production rate up to 1200 boxes an hour

Box transfer speed 22 metres a minute

Electrical power supply three-phase / single-phase

Temperature of use from + 5°C to + 35°C

Overall plan dimensions 1820 x 990 mm

Work surface height 650 mm

Installed power 0,25 kW

Electrical protection IP 54

Pneumatic power supply 6 bar

Air consumption per box cycle 1,5 nl

Weight 293 Kg

*The specifications may be subject to change.

ACCESSORIES

S01 - RUL - S02 - S04 - S10 - S15 - S08 - S17 - S09 - S21

ASM Sweden AB

Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel.

040 - 22 89 80, Fax 040 - 22 89 60

Försäljningskontor: Göteborg Tel. 0301 - 212 11 Halmstad 035 - 22 78 70 Stockholm Tel. 08

- 647 95 60 Östersund Tel. 063 - 10 46 05

www.asm.eu