



GEM X350



Semiautomatic carton sealer with self-adhesive tape for the top and bottom sealing of random American-type boxes. Particularly suitable for high, low or irregularly shaped boxes. The machine has a device for blocking the box by means of mechanical side arms. The taping machine, combined with outfeed conveyors, represents an effective and economic packaging station.

- Economical
- Strong and rugged construction
- Fast operations
- Optimal sealing
- Easy use
- Simple regulation
- Reduced bulk



TECHNICAL DESCRIPTION

Structure of the main machine part in bolted and painted bent steel. The boxes are driven by 4 flat drive belts, 2 bottom and 2 top, driven by a single motor. The boxes are blocked by the pneumatic actuation of two side arms.

Standard taping heads: T22 or T23 for adhesive tape with width 50mm

Supports: fixed

Box size: L from 150 mm upwards W from 130 to 520 mm H from 100 to 520 mm

Production rate max 600 boxes/h

Box transfer speed 22 metres a minute

Electrical power supply three-phase/single-phase

Temperature of use From +5°C to +35°C

Electrical protection IP 54

Installed power 0,23 kW

Pneumatic power supply 6 bar

Air consumption per box cycle 6 nl

Overall plan dimensions 1790 x 1000mm

Work surface height 650 mm

Weight 240 kg

*The specifications may be subject to change.

ACCESSORIES

S01, TAPING HEADS - S04, Casters - S08, Lower closure cover - S09, Wired roll holder kit with sensors - S10, RFC kit -

S16, Belts switching off kit - RUL, Roller conveyors for box entrance and exit

ASM Sweden AB

Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel. 040 - 22 89 80, Fax 040 - 22 89 60

Försäljningskontor: Göteborg Tel. 0301 - 212 11 Halmstad 035 - 22 78 70 Stockholm Tel. 08 - 647 95 60 Östersund Tel. 063 - 10 46 05

www.asm.eu