



GEM X520

Automatic self-dimensioning carton sealer with self-adhesive tape for top and bottom sealing of random American-type boxes. The machine can be used by non-specialist staff and, if combined with infeed and outfeed conveyors, represents a simple, effective and economical packing station. The machine, when combined with automatic devices for centring and regulating the flow of boxes (DAC 520), can also work in lines not controlled by operatives.

- Economical
- Strong and rugged
- Fast operations
- Optimal sealing
- Easy use
- Simple regulation
- Reduced bulk



TECHNICAL DESCRIPTION

Main machine structure in bent, bolted and painted sheet steel. The boxes are fed by means of two lower side drive belts driven by a single motor. The regulations for the various formats are carried out by means of handwheels.

Standard taping heads: T22 or T23 for adhesive tape with width 50mm

Safety guards: aluminium section bar and transparent methyl acrylate panels

Supports: fixed

Box size: L from 180 mm upwards W from 100 to 510 mm H from 100 to 510 mm

Production rate up to 350/500 boxes an hour

Box transfer speed 27 metres a minute

Electrical power supply three-phase / single-phase

Temperature of use from + 5°C to + 35°C

Installed power 0,23 kW

Electrical protection IP 54

Pneumatic power supply 6 bar

Air consumption per box cycle 6,5 nl

Overall plan dimensions 1562 x 1014 mm

Work surface height 650 mm

Weight 210 Kg

*The specifications may be subject to change.

ACCESSORIES

S01 - S02 - S04 - S06 - S09 - S10 - S11 - S12 - S13 - S17 - RUL

ASM Sweden AB

Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel.

040 - 22 89 80, Fax 040 - 22 89 60

Försäljningskontor: Göteborg Tel. 0301 - 212 11 Halmstad 035 - 22 78 70 Stockholm Tel. 08

- 647 95 60 Östersund Tel. 063 - 10 46 05

www.asm.eu