



HM F 520 T

Automatic carton sealer with manual dimensioning and flap closer for sealing with hot glue. It glues and folds the four upper flaps of uniform size, American-type boxes. The regulations are fast and easy. To be used on fully automatic lines, without the control of operatives. The machine is designed to be combined with the melting and glue application units most widely available on the market.

- Strong and rugged
- Fast operations
- Optimal sealing
- Easy use
- Reduced bulk
- Minimum maintenance
- Simple regulation

TECHNICAL DESCRIPTION

Main machine structure in bent, bolted and painted sheet steel. The boxes are fed by means of two lower side drive belts driven by a single motor. The regulations for the various formats are carried out by means of handwheels.

Box feed : 2 side drive belts, parallel and self-centring

Safety guards : aluminium section bar and panels in transparent methyl acrylate with safety microswitches

Supports : fixed

Pressing of glued flaps : mobile pneumatic presser

Box size : L from 250 to 600 mm W from 150 to 520 mm H from 100 to 670 mm

Production rate up to 1200/1300 boxes an hour

Box transfer speed 28 metres a minute

Electrical power supply three-phase / single-phase

Temperature of use from + 5°C to +35°C

Installed power (not including melting/glue application unit) 0,25 kW

Electrical protection IP 54

Pneumatic power supply 6 bar

Air consumption per box cycle 1,5 nl

Overall plan dimensions 2350 x 1000 mm

Work surface height 650 mm

Weight 380 kg

*The specifications may be subject to change.

ACCESSORIES

RUL - S02 - RLC 50 - S04 - S15

ASM Sweden AB

Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel.

040 - 22 89 80, Fax 040 - 22 89 60

Försäljningskontor: Göteborg Tel. 0301 - 212 11 Halmstad 035 - 22 78 70 Stockholm Tel. 08

- 647 95 60 Östersund Tel. 063 - 10 46 05

www.asm.eu