



## **JUNIOR**

Semiautomatic carton sealer with autoadhesive tape for the top and bottom sealing of American-type boxes, for uniform carton size batches, manual dimensioning. The adjustments are fast and easy, also allowing its use by non-specialist operators. The machine, if combined with infeed and outfeed conveyors, represents a simple, fast and economical packaging station.

- Economical
- Strong and rugged
- Fast operations
- Optimal sealing
- Easy use
- Simple regulation
- Reduced bulk

## **TECHNICAL DESCRIPTION**

Structure of the main machine part in bolted and painted bent steel sheet. The boxes are driven by means of a lower side drive belt and by a high-flow bucking surface.

Standard taping heads: new head TJ 56 for self-adhesive tape width 50 mm and front edge 60mm.

Supports: with wheels (diam. 60 mm) (two wheels equipped with brake)

Dimensions of the boxes to be taped: L from 180 mm upwards; W from 100 to 400 mm; H from 120 to 400mm

Production rate 1000/1200 boxes per hour

Box transfer speed 19 metres a minute

Electrical power supply 0,18 kW

Temperature of use From +5°C to +35°C

Electrical protection IP 54

Installed power 0,18 kW

Overall plan dimensions 750 x 790 mm

Work surface height 650 mm

Weight 92 kg

\*The specifications may be subject to change.

## **ACCESSORIES**

S19 - S20

## **ASM Sweden AB**

Huvudkontor & lager: Box 9182, 200 39 MALMÖ. Bronsyxegatan 9 , 213 75 MALMÖ Tel. 040 - 22 89 80, Fax 040 - 22 89 60

Försäljningskontor: Göteborg Tel. 0301 - 212 11 Halmstad 035 - 22 78 70 Stockholm Tel. 08 - 647 95 60 Östersund Tel. 063 - 10 46 05

**[www.asm.eu](http://www.asm.eu)**